


|  |  |   |
|--|--|---|
|   | <b>JP8121734</b>   | <b>esp@cenet</b>  |
|  | <b>METHOD OF CARBONIZING/INCINERATING TREATMENT OF SLUDGE AND THE LIKE AND DEVICE THEREFOR</b> |   |
|  | Patent Number:   | JP8121734   |
|  | Publication date:  | 1996-05-17  |
|  | Inventor(s):   | WAKIYA KAZUNORI   |
|  | Applicant(s):  | OKAWARA MFG CO LTD  |
|  | Requested Patent:  | JP8121734   |
|  | Application Number:  | JP19940282526 19941021  |
|  | Priority Number(s):  |   |
|  | IPC Classification:  | F23G7/00 ; F23G7/00 ; C02F11/00 ; F23G5/00 ; F23G5/00 ; F23G5/02 ; F23G5/50 |
| EC Classification:   |  |   |
| Equivalents:   |  |   |
| <b>Abstract</b>  |  |   |
| <p><b>PURPOSE:</b> To provide the method of carbonizing/incinerating treatment of sludge and the like and the device therefor, capable of carbonizing and incinerating matters to be treated, comparatively inexpensively and at a very small expense for fuel.</p> <p><b>CONSTITUTION:</b> The carbonizing/incinerating treatment of sludge and the like is effected by a method wherein a single combustion furnace 2 is employed and the carbonizing and incinerating treatments are effected by regulating the supplying amount of combustion air A, supplied into the combustion furnace 2. On the other hand, the carbonizing/incinerating treatment device 1 of the present invention is provided with only one combustion furnace 2 while the supplying route 18 of combustion air is constituted of a route 18T for carbonizing and another route 18S for incinerating.</p> |  |   |
| Data supplied from the esp@cenet database - 12   |  |   |